

SURVEY RECOVERY FORM

City of Everett
Department of Public Works

State of Washington
County: Snohomish

Station Name: 694 77 05

Horizontal Datum: NAD83/91
Vertical Datum: NAVD88

Established By: Perteet
Engineering Inc.

Control Point ID: Book: 694 Page: 77 Pt#: 02 Date: 11/18/99

Edited by Geodetic Consultants, 03/22/2000.

Section: 20 Township: 29N Range: 5 E

LATTITUDE: (5 decimal places) 47 58 43.39486
LONGITUDE: (5 decimal places) 122 12 20.63885

ORTHOMETRIC HEIGHT: _____ Feet
_____ Meters

Washington State Plane Coordinates – North Zone

	Northing (4 decimal places)	Easting (4 decimal places)	Point Scale Factor (to 9 decimal places)	Convergence Deg Min Sec
Feet	360004.474	1304305.544	0.999945193	-01 01 18.4
Meters	109729.5833	397553.1253		

HORIZONTAL DATA:

Horizontal position established by: Perteet Engineering Inc.

_____ resection survey, comments _____
_____ GPS survey, GPS adjustment software used: _____
x _____ other, explain: Closed traverse

surveyor's estimated relative positional accuracy: 0.1 ft n @ 0.1 ft E 95% confidence Level

surveyor's estimated absolute positional accuracy: 0.5 ft @ 1 sigma _____ @ _____ % confidence

VERTICAL DATA:

Vertical position established by:

_____ differential leveling to: _____ order accuracy
_____ GPS survey, accuracy within _____ ft _____ meters

surveyor's estimated relative positional accuracy: _____ ft @ _____ 95% confidence Level

surveyor's estimated absolute positional accuracy: _____ ft @ _____ 95% confidence

Correction to NGVD29: -1.122m.

MONUMENT DESCRIPTION

A concrete monument with a brass pin in lead, set under an iron monument case and cover. That is 22 feet East and 194 feet South of the center of the intersection.

TO REACH

Located south of the intersection of Rockefeller Avenue and Hewitt Avenue.

REFERENCES

Az from North	Distance	Reference Description
---------------	----------	-----------------------

Month & Year Recovered:

Condition of Mark:

Recovered By:

